FARMTRAC

YOUR GO-TO TRACTOR FOR EVERY CHALLENGE

Power-Packed with 3-Cylinder

Master Control With 9 F + 3 R Constant Mesh Transmission

Lift Heavy with Ease – 800 kg Capacity

FARMTRAC 30 (4WD)		
ENGINE	Make	Mitsubishi
	No. of Cylinders	3
	Tractor Horsepower	28.5
	Displacement (cc)	1318
	Rated RPM	2800
	Emission Norms	Stage 3A
	Aspiration	Natural Aspiration
	Fuel tank capacity (Ltrs.)	24
	Air cleaner	Dry Type
TRANSMISSION	Gear	9 F + 3 R
	Type	Constant Mesh
REAR AXLE	Type	Bull Grear Reduction
	Differential Lock	Yes
SPEED : FORWARD (KM/H) MAX./MIN		Max.20.36 / Min 1.28 (Agri.), Max.18.4 / Min 1.2 (Turf), Max. 18.6 / Min. 1.2 (Ind.)
CLUTCH TYPE		Single Clutch
BRAKE TYPE		OIB
PTO	Speed (rpm)	540 @ 2504 / 540 E @ 2035 ERPM
	Type	Dual PTO
3-POINT HITCH		CAT I N
STEERING	Type	Power Steering
HYDRAULIC	Control system	Position & Draft Control
	Lift Capacity - at lower link end (kg)	800 kg
	Standard auxiliary valve	1DA Convertible with Detent
TYRE	Front Tyre	6*12 (Agri.), 23*8.5-12 (Turf, Ind.)
	Rear Tyre	8.3*20 (Agri.), 33*15.5-16.5 (Turf, Ind.)
DIMENSIONS (+/-2%)	Overall length (mm)	2465 (Agri.), 2677 (Turf, Ind.)
	Overall width (mm)	1041 (Agri.), 1413 (Turf, Ind.)
	Overall height (mm)	2192 (Agri.), 2162 (Turf, Ind.)
	Wheel base (mm)	1551 (Agri., Turf, Ind.)
OPTIONAL FEATURES		
Rear wheel weight		No
Front weight		4 * 30 kg (Optional)
Front weight Carrier		Hanger
Driver seat		E-Marked with Seat Belt
Rear tow hook		No
Swinging draw bar		Yes
ROPS		Yes
Canopy		No
Safety Start Switch Neutral - Gear		No
Battery		12 V, 65 AH

Farmtrac International Business Division
15/5, Mathura Road, Faridabad (NCR), India | Phone: +91-129-2575507/5292
Website: www.escortskubota.com | E-mail: ekl_ex.internationalbusiness@escortskubota.com

Follow Us: Farmtrac Tractors farmtrac_worldwide Farmtrac Worldwide

Disclaimer: Product specifications and features are subject to changes due to continuous development.

Scan for more details